

Confidea F-CS

Confidea Flushmount Channel Selector



Description

The Confidea F-CS is Televic's delegate panel for passive listening in systems with simultaneous interpretation.

Its small form factor, housed in an elegant casing, permits a minimalistic integration into any meeting room furniture. What's more, the unit can be mounted in landscape or in portrait, i.e. in case of integration in armrests of auditorium seats.

A 3.5 mm jack socket is available to connect headphones or a hearing loop for the hearing impaired. For simultaneous interpretation, the panel has a channel selector and headphones volume adjustment. The information display shows the channel number and ISO code of the selected language and the volume setting.

Benefits

The Confidea F-CS is a sleek and discreet solution that is perfectly suited integrate in any context, from desks to armrests in auditorium seats. The ability to connect headphones, which also provides accessibility for the hearing impaired. The clear and easy channel selector allows for user-friendly simultaneous interpretation conferences.

The unit is available in a variety of custom colors, sizes and finishes to blend in neatly in any environment. The Confidea F-CS is backed by the Plixus® network and redundant cabling to ensure maximum reliability.

Features

- » Passive listening function
- » Interpretation function
- » Headphone volume adjustment
- » Language channel selector (64 channels available)
- » Channel information display
- » Rounded corners for easy installation
- » Trademark natural Televic Sound
- » Landscape or portrait mounting (desks or armrests)
- » Available in custom colors, sizes, finishes

Connectivity

- » Two RJ 45 connectors for loop through cabling
- » 3.5 mm stereo jack socket for headphones
- » Plixus-powered

Software

- » To fully configure, manage, and use the unit, Televic's CoCon management software is required. The following standard licenses are available:

CoCon Discussion **71.98.1101**

CoCon Interpretation **71.98.1107**

Certifications

Region	Certification
Europe	CE

Specifications

Mechanical	
Material	Steel
Color	Tiger coating carbon 01
Size (mm)	155 (w) × 50 (h) × 30 (d)
Size packed (mm)	205 (w) × 85 (h) × 40 (d)
Weight	220g
Weight packed	280g
Electrical	
Voltage	48 VDC
Current consumption	2 W
Headphone Output	
Maximum output	> 10 mW
Frequency response	22-22,000 Hz
Dynamic range	> 90 dB
THD @ nominal level	< 0.1%
Load impedance	16-32 Ω

Technical Drawing

