

## 2M HIGH SPEED HDMI CABLE, ANTHRA LINE



### LINDY International Limited

Sadler Forster Way  
Teesside Industrial Estate  
Stockton-on-Tees, TS17 9JY  
United Kingdom

T +44 1642 754020  
postmaster@lindy.com  
lindy.com

Subject to technical  
modifications and  
other changes.

### DESCRIPTION

From the Lines cable connectivity concept developed by Lindy, Anthra Line HDMI cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line HDMI cables are premium connections that feature triple shielded with 30AWG copper conductors for performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 8bit are supported. Anthra Line HDMI cables are also capable of transmitting 32 channel audio and Dolby® True HD.

The HDMI 2.0 specification is supported for 18Gbps bandwidth capacity in cable lengths up to 5m.

Anthra Line HDMI cables are available in lengths from 0.3m to 5m.

### FEATURES

- Professional choice High Speed HDMI 2.0 cable for commercial and high performance AV and IT installations
- Supports UHD resolutions up to 4096x2160@60Hz and HDTV resolutions up to 1080p
- Robust PVC housing, 24K gold plated connectors and contacts
- Triple shielded cable, corrosion resistant tinned copper 30AWG conductors
- HDMI 2.0 compliant: 3D, 4K, 18Gbps, HEC, ARC, CEC, Dolby® True HD, DTS-HD Master Audio; HDMI ATC certified
- 10 year warranty

### CERTIFICATES



## 2M HIGH SPEED HDMI CABLE, ANTHRA LINE

### CONNECTORS

Connector A	HDMI Type A Male
Connector B	HDMI Type A Male
Housing Material	PVC
Connector Plating	24K Gold 3µm
Pin Construction	Phosphor Copper
Pin Plating	24K Gold 3µm
Dimensions (approx.) WxDxH	20x34.2x10.9mm (0.79x1.35x0.43in)

### CABLE CONSTRUCTION

Length	2m (6.56ft)
Standard	High Speed HDMI with Ethernet
Colour	Black
Type	Round
Jacket Diameter	6.0mm (0.24in)
Jacket Material	PVC
Conductor Material	Copper
Conductor Gauge	30AWG
Shielding	Copper Braid, 65%

### SPECIFICATIONS

Supported Bandwidth	18Gbps
Maximum Resolution	4096x2160@60Hz 4:4:4 8bit
Nominal Attenuation	300kHz-825MHz <5dB 825MHz-2.475GHz <5dB 2.475GHz-4.125GHz <12dB 4.125GHz-5.1GHz <20dB
Minimum Bend Radius	48mm (1.89in)
Operating Temperature	-10°C - 80°C (14°F - 176°F)
Storage Temperature	-10°C - 80°C (14°F - 176°F)
ATC Approved	Yes

### MISCELLANEOUS

Packaging Type	Polybag
Warranty (Years)	10

### PURCHASING INFORMATION

No.	36963
EAN	4002888369633

This product is available in these lengths:  
36960 – 0.3m (0.98ft), 36961 – 0.5m (1.64ft), 36962 – 1m (3.28ft),  
36963 – 2m (6.56ft), 36964 – 3m (9.84ft), 36965 – 5m (16.44ft)



Cable front view