

ZU920TST

Ultra-Bright fixed lens laser projector



- **9,800 Lumen Duracore laser projector - Ultra bright for immersive installations**
- **Full motorised lens shift - Ideal for a simple set up**
- **Large zoom range - Motorised zoom expands placement opportunities**
- **Long life - Delivers 30,000 hours of virtually maintenance-free operation**

At 9,800 lumens with 4K and HDR compatibility, the ZU920TST features a dust-resistant IP5X certified optical engine for 24/7 operation capabilities, offering true maintenance-free projection for up to 30,000 hours of powerful performance in Eco mode. Other features include a motorised zoom, full motorised lens shift and built-in dual 10W speakers.

High brightness, colour precision and quiet operation, along with a short throw lens make this projector the ideal solution for a variety of end-user scenarios and professional environments, such as short throw digital signage, edge-blending and projection mapping, simulation, and immersive installations.

The added control flexibility of HDBaseT and LAN make this projector an affordable install and forget solution.

Specifications

Display/imagen	
Tecnología de visualización	DLP
Resolución	WUXGA (1920x1200)
Brillo	9.800 lumens
Brillo ANSI	8.200
Ratio de contraste	3.000.000:1
Ratio de contraste - on/off	1.100:1
Relación de aspecto nativo	16:10
Ratio de aspecto - compatible	4:3,16:9,16:10
Corrección Keystone - Horizontal	30°
Corrección Keystone- Vertical	30°
Uniformidad	95%
Tamaño de pantalla	1.27m ~ 7.62m (50" ~ 300") diagonal
Info Lámpara	
Fuente de luz	DuraCore Laser
Vida del LÁSER	30.000horas
Óptica	
Distancia de tiro	0.65:1 ~ 0.75:1
Distancia de proyección (m)	0.7m - 16.6m
Zoom	1.15
Tipo de zoom	Motorizado
Distancia focal (mm)	9.69~11.19
Cambio de lente	Vertical: +/-55%, Horizontal: +/-25%
Offset nativo	50%
Lenshift	Yes - {{downloads_link}}
Conectividad	
Conexiones	<p>Inputs 1 x HDBaseT, 1 x HDMI 2.0, 1 x HDMI 2.0, 1 x VGA, 1 x Sincronización 3D, 1 x Audio 3.5mm</p> <p>Outputs 1 x HDMI 2.0, 1 x Sincronización 3D, 1 x Alimentación USB-A 1.5A, 1 x Audio 3.5mm</p> <p>Control 1 x 12V trigger, 1 x Remoto por cable, 1 x RJ45, 1 x RS232</p>
General	
Nivel sonoro (típico)	36dB
Nivel sonoro (max)	38dB
Seguridad	Security bar, Kensington Lock
Idiomas OSD / display	10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional)
Operatividad 24/7	Yes
Operatividad 360°	Yes
Control remoto	Mando ProAV retroiluminado
Altavoces	2
Wattios por altavoz	10W
Networking	
LAN - red inalámbrica	No
LAN	Yes
Corriente	
Fuente de alimentación	AC 90 – 264V 50/60 Hz
Consumo energético (mín.)	260W
Consumo energético (máx.)	505W
Peso y dimensiones	
Dimensiones (ancho x profundidad x alto)	480 x 144 x 376
Peso bruto	17.5 kg
Peso neto	14 kg

