

# ZU920T

Ultra bright fixed lens laser projector

---



- **9800 lumen DuraCore laser projector - Ultra bright for immersive installations**
- **Full motorised lens shift - Ideal for a simple set-up**
- **Large zoom range - Motorised zoom expands placement opportunities**
- **Long life - Delivers 30,000 hours of virtually maintenance-free operation**



At 9,800 lumens with 4K and HDR compatibility, the ZU920T features a dust-resistant IP5X certified optical engine for 24/7 operation capabilities, offering true maintenance-free projection for up to 30,000 hours of powerful performance in Eco mode. Other features include a motorised zoom, full motorised lens shift and built-in dual 10W speakers.

High brightness, colour precision and quiet operation, along with a short throw lens make this projector the ideal solution for a variety of end-user scenarios and professional environments, such as short throw digital signage, edge-blending and projection mapping, simulation, and immersive installations.

## Specifications

<b>Display/imagen</b>	
Tecnología de visualización	DLP
Resolución	WUXGA (1920x1200)
Brillo	9.800 lumens
Brillo ANSI	8.200
Ratio de contraste	3.000.000:1
Ratio de contraste - on/off	1.100:1
Relación de aspecto nativo	16:10
Ratio de aspecto - compatible	4:3,16:9,16:10
Corrección Keystone - Horizontal	30°
Corrección Keystone- Vertical	30°
Uniformidad	95%
Tamaño de pantalla	1.27m ~ 7.62m (50" ~ 300") diagonal
<b>Info Lámpara</b>	
Fuente de luz	DuraCore Laser
Vida del LÁSER	30.000horas
<b>Óptica</b>	
Distancia de tiro	1.25:1 ~ 2:1
Distancia de proyección (m)	1.33m - 13.06m
Zoom	1.6
Tipo de zoom	Motorizado
Distancia focal (mm)	18.72~29.59
Cambio de lente	Vertical: +/-55%, Horizontal: +/-25%
Offset nativo	50%
Lenshift	Yes - <a href="#">{{downloads_link}}</a>
<b>Conectividad</b>	
Conexiones	<b>Inputs</b> 1 x HDBaseT, 2 x HDMI 2.0, 1 x VGA, 1 x Sincronización 3D, 1 x Audio 3.5mm <b>Outputs</b> 1 x HDMI 2.0, 1 x Sincronización 3D, 1 x Alimentación USB-A 1.5A, 1 x Audio 3.5mm <b>Control</b> 1 x 12V trigger, 1 x Remoto por cable, 1 x RJ45, 1 x RS232
<b>General</b>	
Nivel sonoro (típico)	36dB
Nivel sonoro (max)	38dB
Seguridad	Security bar, Kensington Lock
Idiomas OSD / display	10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional)
Operatividad 24/7	Yes
Operatividad 360°	Yes
Control remoto	Mando ProAV retroiluminado
Altavoces	2
Wattios por altavoz	10W
<b>Networking</b>	
LAN - red inalámbrica	No
LAN	Yes
<b>Corriente</b>	
Fuente de alimentación	AC 90 – 264V 50/60 Hz
Consumo energético ( mín.)	260W
Consumo energético ( máx.)	505W
<b>Peso y dimensiones</b>	
Dimensiones (ancho x profundidad x alto)	480 x 144 x 376
Peso bruto	17.5 kg
Peso neto	14 kg

