


# ZU1300

Spectacular image quality, low maintenance and ultimate reliability



- **High brightness WUXGA DLP projector with DuraCore laser technology**
- **Up to 30,000 hours laser light source**
- **Dust resistant – Independently tested, IP6X certified for total reliability**
- **Installation flexibility – 7x lens options including ultra short throw**



The ZU1300 offers enhanced features such as built-in edge-blending and warping as well as 4K HDR compatibility. Part of the DuraCore laser line up, it combines a longer-lifetime light source and an independent IP-rated dust certification for ultimate peace of mind. Delivering up to an astonishing 30,000 hours , this projector achieves superior color rendition producing visually striking lifelike images with exceptional detail.

# Specifications

UPC: 796435 44 609 3, EAN: 5055387666337, Colour: Black

The following specifications are preliminary and subject to change without notice

## Display/image

|                                  |                   |
|----------------------------------|-------------------|
| Display technology               | DLP™              |
| Resolution                       | WUXGA (1920x1200) |
| Brightness                       | 14,400 lumens     |
| ANSI brightness                  | 12,000            |
| Contrast ratio                   | 2,000,000:1       |
| Native aspect ratio              | 16:10             |
| Aspect ratio - compatible        | 4:3, 16:9, 16:10  |
| Keystone correction - horizontal | +/-20°            |
| Keystone correction - vertical   | +/-20°            |
| Uniformity                       | 90%               |
| Screen size                      | Dependent on lens |

## Lamp info

|                   |              |
|-------------------|--------------|
| Light source type | Laser        |
| LASER life        | 30,000 hours |

## Optical

|                     |   |
|---------------------|---|
| Throw ratio         | Dependent on lens   |
| Projection distance | Dependent on lens   |
| Lens options        | BX-CTA16- 0.36 ~ 0.36<br>BX-CTA17- 0.65~0.75<br>BX-CTA15- 0.75 ~ 0.95<br>BX-CTA01- 0.95 ~ 1.22<br>BX-CTA06- 1.22 ~ 1.53<br>BX-CTA03- 1.52 ~ 2.92<br>BX-CTA13- 2.90 ~ 5.50 |
| Lens shift          | Yes - <a href="#">{{downloads_link}}</a>  |

## Connectivity

|             |  |
|-------------|--|
| Connections | <b>Inputs</b> 2 x HDMI, 1 x 3D sync, 1 x DVI-D, 1 x HDBaseT, 1 x 3G-SDI<br><b>Outputs</b> 1 x 3D sync, 1 x HDMI<br><b>Control</b> 1 x RS232, 1 x Wired remote, 1 x USB-A power 2A, 1 x 12V trigger, 1 x RJ45 |
|-------------|--|

## General

|                          |   |
|--------------------------|---|
| Noise level (typical)    | 37dB  |
| Noise level (max)        | 39dB  |
| PC compatibility         | HD, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible  |
| 2D compatibility         | PAL (625/576i/p), SECAM, NTSC (525/480i/p), HDTV (720p, 1080i/1080p)  |
| 3D compatibility         | Side-by-Side: 1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60                       |
| 3D                       | Full 3D   |
| Security                 | Security bar, Kensington Lock   |
| IP rating                | IP6X  |
| OSD / display languages  | 11 languages: Dutch, English, French, German, Indonesian, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish |
| 24/7 operation           | Yes   |
| 360° operation           | Yes   |
| Operating conditions     | 5°C~40°C/41°F~104°F, max altitude M/0ft, max humidity 10-85%  |
| Remote control           | Wired ProAV remote  |
| In the box               | AAA Battery, AC power cable 3M, Lens cover, VGA cable 1.8m, User manual CD, Quick start guide                                   |
| Optional wireless models | QuickCast Bundle, QuickCast starter kit   |

## Networking

|     |     |
|-----|-----|
| LAN | Yes |
|-----|-----|

## Power

|                             |                       |
|-----------------------------|-----------------------|
| Power supply                | 100 - 240V, 50 - 60Hz |
| Power consumption (standby) | 0.5W                  |
| Power consumption (min)     | 465W                  |
| Power consumption (max)     | 955W                  |

## Weight and dimensions

|                        |  |
|------------------------|--|
| Dimensions (W x D x H) | 484 x 529 x 208 mm / 19.06" x 20.83" x 8.19" |
| Gross weight           | 27 kg / 59.52 lbs                            |
| Net weight             | 21 kg / 46.3 lbs                             |

