

COMPARATIVA POSICIONADORES DATAVIDEO ABRIL 2024

Modelo	PTR-15	PTR-10 MARK II	PTR-10T MARK II
Codigo Crambo	95685	83791	83792
Product	4K Robotic Pan Tilt Head	Robotic Pan Tilt Head	HDBaseT Robotic Pan Tilt Head
URL	https://www.datavideo.com/eu/product/PTR-15	https://www.datavideo.com/eu/product/PTR-10+MARK-II	https://www.datavideo.com/eu/product/PTR-10T+MARK-II
Video Interface	HDMI 2.0 x 1 12G-SDI x 1 3G-SDI x 1	HDMI x 1 SDI x 1	HDMI x 1 SDI x 1 RJ45 x 1 (HDBaseT)
Video Output	2160p 60/59.94/50 2160p 30/29.97/25 1080p 60/59.94/50 1080p 30/29.97/25 1080i 60/59.94/50 720p 60/59.94/50"	2160p 29.97/25 1080p 59.94/50 1080i 59.94/50 720p 59.94/50	2160p 29.97/25 1080p 59.94/50 1080i 59.94/50 720p 59.94/50
Control Unit	RMC-180 MARK II RMC-300A RMC-300C SHOWCAST 100 VISCA Protocol Controller IP Control IR remote	RMC-180 RMC-300A RMC-300C ShowCast 100 VISCA Protocol Controller IP Control IR remote	RMC-180 HS-1600T HS-1600T Mark II RMC-300A VISCA Protocol Controller IP Control IR remote
Genlock	YES	---	---
Timecode	YES	---	---
Panning / Tilting Range	Pan: 340° Tilt: ±45°	Pan: 340° Tilt: ±45°	Pan: 340° Tilt: ±45°
Panning / Tilting Speed	Pan: 0.12~15° /Sec Tilt: 0.06~10° /Sec	Pan: 0.12~15° /Sec Tilt: 0.06~10° /Sec	Pan: 0.12~15° /Sec Tilt: 0.06~10° /Sec
Preset	Pan/Tilt position 199	Pan/Tilt position 50	Pan/Tilt position 50
Control Distance	1,200M by RS422 100M by DVIP	1,200M by RS422 100M by DVIP	1,200M by RS422 100M by HDBaseT
Control Protocol	Sony VISCA DVIP	Sony VISCA DVIP	Sony VISCA DVIP
Control Input	RS-422 DVIP	RS-422 DVIP	RS-422 HDBaseT
Maximum Load	4 KG Max	4 KG Max	4 KG Max
Control Output	RS-232 RS-422 IP Control BX-Lens LanC	RS-232 RS-422 BX-Lens LanC	RS-232 RS-422 BX-Lens LanC
Power Requirement	DC 14V~ 20V, 90W	DC 12V~ 18V, 3A (Without Camera) DC 12V~ 18V, 5A (With Camera)	DC 12V~ 18V, 3A (Without Camera) DC 12V~ 18V, 5A (With Camera)
Power Supply	DC 24/12V, 36W Max	DC 12/10/8.4/7.4V, 24W Max	DC 12/10/8.4/7.4V, 24W Max
Operating Temp. Range	0~40 C°	0~40 C°	0~40 C°
Operating Humidity Range	10~80%	10~80%	10~80%
Storage Temp. Range	-10~60C°	-10~60C°	-10~60C°
Storage Humidity Range	5~80%	5~80%	5~80%
Weight	3.7 kg	3.4 kg	3.4 KG
Dimension (LxWxH)	241 x 191 x 300 mm	230 x 190 x 300 mm	230 x 190 x 300 mm
Optional accessories	ZEK-1 ZEK-2 PCB-1 WM-10 WM-11 CM-10	ZEK-1 WM-10 WM-11 CM-10	ZEK-2 KIT WM-10 WM-11 CM-10
What's in the Box	PTR-15 Main Unit x 1 DC 19V power adaptor x 1 AC cord x 1 IR remote control x 1 DC with lock to D-Tap cable x 1 HDMI cable x 1 SDI cable x 1 Remote cable (2.5mm phone-jack to mini-din 8pin) x 1 1/4" screw x 2 1/4" to 3/8" screw adaptor x 1	PTR-10 Mark II Main Unit x 1 DC 12V power adaptor x 1 AC cord x 1 IR remote control x 1 DC with lock to D-Tap cable x 1 HDMI cable x 1 SDI cable x 1 Remote cable (2.5mm phone-jack to mini-din 8pin) x 1 1/4" screw x 2 1/4" to 3/8" screw adaptor x 1	PTR-10T Mark II Main Unit x 1 DC 12V power adaptor x 1 AC cord x 1 IR remote control x 1 DC with lock to D-Tap cable x 1 HDMI cable x 1 SDI cable x 1 Remote cable (2.5mm phone-jack to mini-din 8pin) x 1 1/4" screw x 2 1/4" to 3/8" screw adaptor x 1