

# HC-X1600

X1600

X1200

## Versatile 4K 60p Camcorder

The Handle Unit can be used as an optional accessory.



1

### 4K 60p with High Mobility and Operability

Light weight 0.85kg Body, High Operability Layout Design, 1/2.5-type 8.29M MOS Sensor, 4K 60p 420-10bit (HEVC)

2

### Optical 24x Zoom and Fast Face Detection AF

Wide 25mm (4K/FHD), iZoom 48x (FHD)/32x (4K), 4K High Precision AF, Face Detection AF/AE, 5-Axis HYBRID O.I.S. (UHD/FHD), Internal ND Filter

3

### Pro Quality Interface and Network Availability

XLRx2,\*1 Wi-Fi 5GHz/2.4GHz, RTP/RTSP/RTMP/RTMPS, Easy Detachable Handle, Long Life Battery, USB PD, Double SD Memory Card Slot

\*1 The optional handle unit is needed.

Recording Format

Lens

Sensor / Engine

Monitor

4K

AVCHD Progressive

MP4 MOV

24x  
Optical Zoom

32x  
iZOOM  
(UHD)

25mm  
Wide Angle  
(UHD/FHD)

1/2.5-inch  
8.29M  
MOS

VENUS  
Engine

3.5-inch  
2760K dot

Face Detection AF/AE	5-AXIS HYBRID O.I.S.	4K HIGH PRECISION AF	ND Filter	Two Manual Rings	HEVC 10bit Rec	4K 60p (MOV/MP4)	420-10bit (4K/60P) 422-10bit (4K/30P)	120fps Super Slow	IR Shooting*2
LED Light optional	2 x XLR IN optional	24bit PCM AUDIO	Double SD Card Slot	NEW USB PD	NEW 0.39" OLED EVF (1,770K)	Live Streaming (RTSP/RTMP/RTMPS)	NEW Built-in Wi-Fi (5GHz/2.4GHz)		

\*2 The commercially available IR light is needed separately.